



**Available Now from
Richardson RFPD!**

A2200-A

Positioning Product

GPS Receiver Modules
Telematics Platforms



SiRFstarIV - GPS Module: The Answer to All Challenges

The A2200 GPS modules enable fastest acquisition and tracking with the latest SiRFstarIV technology. In any case the module fully answers the demand for lowest power consumption with – amongst other features – SiRFaware™ technology. The removal of jammers does not only facilitate designs of new products, but guarantees operation even in hostile environments. Highest sensitivity, during acquisition or while tracking, allows for use in many different environments and under toughest conditions.

Features

- Complete GPS module
- Jamming detection and removal
- Rom-based design
- Best acquisition sensitivity
- Lowest tracking power consumption
- SiRFaware™ for constant Hot Start

Benefits


- Easy integration
- Minimal BOM
- Minimal BOM
- Ideally suited for all small battery powered GPS applications

Your Global Source for
RF, Wireless & Energy Technologies



www.richardsonrfpd.com | 800.737.6937 | 630.208.2700

With the mission to support our customers in implementing GPS functionality into their systems, Maestro Wireless Solutions is offering a distinct product portfolio to address a wide area of applications. These range from traditional telematics solutions to latest highly integrated consumer devices, all of them having their special requirements towards a GPS module. Based on SiRFstarIII and SiRFstarIV chip sets, Maestro Wireless Solutions GPS module solutions address different specific needs and combine high performance, low power consumption, and simplified integration effort. Our modules comply with the RoHS standard and are 100% electrically and functionally tested prior to packaging, thereby assuring the guarantee of the highest quality products.



PERFORMANCE

Channels	48
Correlators	~ 400,000
Frequency	LI - 1,575 MHz
Sensitivity¹	
Tracking	- 163 dBm
Navigation	- 160 dBm
Acquisition (cold start)	- 148 dBm
Position Accuracy² (horizontal)	< 2.5 m CEP (autonomous) < 2.0 m CEP SBAS
Time To First Fix	
Hot Start ³	< 1 s
Warm Start ³	< 32 s
Cold Start ³	< 35 s

COMMUNICATION

UART - NMEA (Default)	
NMEA message Switchable	GGA, RMC, GSA, GSV, VTG, GLL, ZDA
Baud rate Switchable	4,800 (default) 1,200 to 115.2k
Ports	Tx (NMEA output) Rx (NMEA input)
UART - SiRF Specific SSB/OSP	
SiRFbinary protocol	Protocol for SiRFstar product family up to SSIII
Open Socket Protocol	Protocol extension for SiRFstarIV
Baud rate Switchable	57.6k (default) 1,200 to 115.2k
Ports	Tx (Binary output) Rx (Binary input)
SPI - NMEA/SiRF Specific (in preparation for A)	
Clock	Up to 6.8 MHz
Ports	DO (NMEA / Binary output) DI (NMEA / Binary input) SPI CLK (clock - input) SPI CS (chip select - input)
SPI - OSP	
Clock	Up to 6.8 MHz
Ports	DO (Binary output) DI (Binary input) SPI CLK (clock - input) SPI CS (chip select - input)

¹) With best matched antenna
²) All SVs with -130dBm

HIGHLIGHTS

SIRFnav™	High availability and coverage; improved TTFF in weak signal environments
SIRFaware™	Keeps module in a state of readiness for rapid navigation (hot start)
Jammer remover technology	Detects and removes up to 8 in-band jammers with minimal loss of sensitivity
A-GPS	Embedded Extended Ephemeris (SiRFInstantFix1) and Ephemeris Push support
MEMS I2C interface	Prepared to use additional sensor information for improved navigation
Flash-based design	Prepared to store configuration and calibration data and to allow firmware updates

POWER

Supply voltage	3.0 to 3.6 VDC
Power consumption	(typical)
Fully tracking	47 mW
Trickle Power Mode (1Hz)	8 mW
SIRFaware™ Mode	500 µW
Hibernate Mode	30 µW
Antenna supply via Vant	Up to 6.8 MHz
Voltage range	up to 5.0V
Max. allowed current ³⁾	50 mA

MECHANICAL

Dimensions	
L x W x H	14 x 10.2 x 2.5 mm ³
L x W x H	0.55" x 0.4" x 0.1"
Weight	1.2 g / 0.04 oz.

ENVIRONMENT

Temperature	
Operating	-40°C to +85°C
Storage	-40°C to +85°C
Humidity	Non condensing

³⁾ External current limiter suggested

Your Global Source for
RF, Wireless & Energy Technologies

RichardsonRFPD
An Arrow Company

www.richardsonrfpd.com | 800.737.6937 | 630.208.2700